



117P7-GT



117P7-GT

RECTIFIER—BEAM POWER AMPLIFIER

Heater	Coated Unipotential Cathodes	
Voltage	117	a-c or d-c volts
Current	0.090	amp.
Maximum Overall Length		3-7/16"
Maximum Seated Height		2-7/8"
Maximum Diameter		1-5/16"
Bulb		T-9
Base	Intermediate Shell Octal 8-Pin	
Pin 1 - No Connection		Pin 6 - Amplifier Cathode
Pin 2 - Heater		Pin 7 - Rectifier Plate, Heater
Pin 3 - Amplifier Plate		Pin 8 - Rectifier Cathode
Pin 4 - Amplifier Grid		
Pin 5 - Amplifier Screen		
Mounting Position		Any

BOTTOM VIEW (8AV)

RECTIFIER UNIT (Half-Wave)

Peak Inverse Voltage	350 max.	volts
Peak Plate Current	450 max.	ma.
D-C Heater to Cathode Potential	175 max.	volts
<i>With Condenser-Input Filter:</i>		
A-C Plate Voltage (RMS)	117 max.	volts
Total Effective Plate-Supply Impedance	15 min.	ohms
D-C Output Current	75 max.	ma.

AMPLIFIER UNIT

Plate Voltage	117 max.	volts
Screen Voltage	117 max.	volts
Plate Dissipation	6.0 max.	watts
Screen Dissipation	1.0 max.	watt
<i>Typical Operation and Characteristics - Class A₂ Amplifier:</i>		
Plate Voltage	105	volts
Screen Voltage	105	volts
Grid Voltage #	-5.2	volts
Peak A-F Grid Voltage	5.2	volts
Zero-Sig. Plate Current	43	ma.
Max.-Sig. Plate Current	43	ma.
Zero-Sig. Screen Current	4	ma.
Max.-Sig. Screen Current	5.5	ma.
Plate Resistance	17000 approx.	ohms
Transconductance	5300	μmhos
Load Resistance	4000	ohms
Total Harmonic Distortion	5.0	%
Max.-Sig. Power Output	0.85	watt

The type of input coupling used should not introduce too much resistance in the grid circuit. With fixed bias, the resistance should not exceed 0.25 megohm; with cathode bias, 0.5 megohm.