

High-Mu Triode

NUVISTOR TYPE

HAVING EXTENDED CUTOFF CHARACTERISTIC

For Use as Grounded-Cathode, Neutralized RF-Amplifier
Tube in Tuners of VHF Television and FM Receivers
Featuring Improved Weak-Signal-Area Reception

GENERAL DATA

Electrical:

Heater Characteristics and Ratings (<i>Design-Maximum Values</i>):		
Voltage (AC or DC)	6.3 ± 0.6	volts
Current at heater volts = 6.3	0.135	amp
Peak heater-cathode voltage:		
Heater negative with respect to cathode.	100 max.	volts
Heater positive with respect to cathode.	100 max.	volts
Direct Interelectrode Capacitances (Approx.):		
Grid to plate	0.92	μf
Grid to cathode, shell, and heater. . .	4.3	μf
Plate to cathode, shell, and heater . .	1.8	μf
Plate to cathode.	0.18	μf
Heater to cathode	1.6	μf

Characteristics, Class A₁ Amplifier:

Plate Supply Voltage.	110	volts
Grid Supply Voltage	0	volts
Cathode Resistor.	130	ohms
Amplification Factor.	63	
Plate Resistance (Approx.).	7000	ohms
Transconductance.	9000	μmhos
Plate Current	6.5	ma
Grid Voltage (Approx.) for plate $\mu_a = 100$.	-5	volts
Grid Voltage (Approx.) for plate $\mu_a = 10$.	-6.8	volts

Mechanical:

Operating Position.	Any
Type of Cathode	Coated Unipotential
Maximum Overall Length.	0.800"
Maximum Seated Length	0.625"
Maximum Diameter.	0.440"
Envelope.	Metal Shell MT4
Socket.	Cinch Mfg. Corp. No. 133 65 10 001, ← Industrial Electronic Hardware Co. No. Nu 5044 or No. Nu 5060, or equivalent
Base.	Medium Ceramic-Wafer Twelvar 5-Pin (JEDEC No. E5-65)


← Indicates a change.



6DS4

Basing Designation for BOTTOM VIEW. 12AQ

- Pin 1^a - Do Not Use
- Pin 2 - Plate
- Pin 3 - Same as Pin 1
- Pin 4 - Grid
- Pin 5 - Same as Pin 1
- Pin 6 - Same as Pin 1
- Pin 7 - Same as Pin 1
- Pin 8 - Cathode
- Pin 9 - Same as Pin 1
- Pin 10 - Heater
- Pin 12 - Heater



AMPLIFIER — Class A₁

Maximum Ratings, Design-Maximum Values:

PLATE SUPPLY VOLTAGE.	300 ^b max.	volts
PLATE VOLTAGE	135 max.	volts
GRID VOLTAGE:		
Negative-bias value	55 max.	volts
Peak-positive value	0 max.	volts
CATHODE CURRENT	15 max.	ma
→ PLATE DISSIPATION:		
With a minimum series plate-circuit resistance of 5000 ohms	1.5 max.	watts
For lower values of series plate- circuit resistance.	See accompanying <i>Plate- Dissipation-Rating Chart</i>	

Typical Operation:

Plate Voltage	70	volts
Grid Supply Voltage	0	volts
Grid Resistor	47000	ohms
Amplification Factor.	68	
Plate Resistance (Approx.).	5440	ohms
Transconductance.	12500	μmhos
→ Plate Current	7	ma

Maximum Circuit Values:

Grid-Circuit Resistance: ^c		
For fixed-bias operation.	0.5 max.	megohm
For cathode-bias operation.	2.2 max.	megohms



^a Pin 1 is of a length such that its end does not touch the socket insertion plane.

→ ^b A plate supply voltage of 300 volts may be used provided sufficient plate-circuit resistance and agc voltage are used to limit the voltage at the plate of the tube to 135 volts under conditions of maximum-rated plate dissipation (1.5 watts).

→ ^c For operation at metal-shell temperatures up to 135^o C.

→ Indicates a change.






92CS-10970R3

NOTE 1: MAXIMUM OUTSIDE DIAMETER OF 0.440" IS PERMITTED ALONG 0.190" LUG LENGTH.

NOTE 2: SHELL TEMPERATURE SHOULD BE MEASURED IN ZONE "A" BETWEEN BROKEN LINES.




PLATE-DISSIPATION-RATING CHART



92CM-11681




AVERAGE PLATE CHARACTERISTICS



92CM-11209



AVERAGE CHARACTERISTICS



92CM-11210

