

ELECTRONIC VALVE SPECIFICATION CV 4043

ISSUE 2 DATED 6.11.56

AMENDMENT NO. 1

Page 2 GROUP B

Screen Grid Current. Under minimum limit,
Amend "3.5" to "0.6"

R.R.E.

November 1960.

NJ.46494/D

Specification NOS /CV4043 Issue 2 Dated 6.11.56 To be read in conjunction with K1001 BS448 & BS1409	<u>SECURITY</u>	
	<u>Specification</u> UNCLASSIFIED	<u>Valve</u> UNCLASSIFIED

Indicates a change →

TYPE OF VALVE - Reliable Beam Tetrode		<u>MARKING</u>	
CATHODE - Indirectly-heated		K1001/4	
ENVELOPE - Glass		<u>BASE</u>	
PROTOTYPE - CV2136		B9A See B.S.448:1953 B9A/1 J	
<u>RATING</u> All limiting Values are absolute		<u>CONNECTIONS</u>	
		Note	
Heater Voltage (V)	6.3	B B C	<u>Pin</u>
Heater Current (A)	0.45		
Max. Anode Voltage (V)	350		1 Control Grid g ¹
Max. Anode Dissipation (W)	13.2		2 Control Grid g ¹
Max. Screen Grid Voltage (V)	310		3 Cathode k
Max. Screen Grid Dissipation (W)	2.3		4 Heater h
Max. Heater-cathode Voltage (V)	490		5 Heater h
Mutual Conductance (mA/V)	4.1		6 No connection NC
Anode Impedance (ohms)	50,000		7 Anode a
Max. Bulb Temperature (°C)	250		8 Screen Grid g ²
Max. Shock (short duration) (g)	500		9 Suppressor g ³
Max. Acceleration (continuous operation) (g)	2.5		
<u>CAPACITANCES (pF)</u>			<u>DIMENSIONS</u>
C _{ag} (max.)	0.5	See B.S.448 : 1953 E9A/2.1 Size Ref No.3	
C _{in} (nom.)	8.5	Dimensions (mm)	
C _{out} (nom.)	7.0	Min. Max.	
		A. Seated height - 60.5	
		C. Diameter 9.0 22.2	
		D. Overall length - 67.5	
		<u>MOUNTING POSITION</u>	
		Any	
<u>NOTES</u>			
B. Measured at V _a = V _{g2} = 250V; V _{g3} = 0; V _{g1} = -12.5V			
C. <u>Note to Electronic Equipment Design Engineers</u> : Special attention should be given to the temperature of valves to be operated in aircraft. Reliability will be seriously impaired if the maximum bulb temperature is exceeded. The life expectancy may be reduced if conditions other than those specified for life test are imposed on the valve and will be reduced appreciably if absolute maximum ratings are exceeded. Both reliability and performance will be jeopardised if heater voltage ratings are exceeded: life and reliability performance are directly related to the degree that regulation of the heater voltage is maintained at its centre-rated value.			

To be performed in addition to those applicable in K1001 and in the specified order unless otherwise agreed by the Inspection Authority

Test Conditions - unless otherwise specified

Vh (V) 6.3
 Va (V) 250
 Vg1 (V) -12.5
 Vg2 (V) 250
 Vg3 (V) 0

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym- bol	Limits						Units
						Min	LAL	Dogey	UAL	Max	ALD	
→ 7.1	Glass Strain	No voltages	6.5	I								
	<u>GROUP A</u> Insulation	Vg1 - all = -100V Vg2 - all = -300V Va - all = -300V		100%	R	100	-	-	-	-		M M M
	Reverse Grid Current	Rg1 = 500k Max		100%	Ig1	-	-	-	-	2.0		uA
	<u>GROUP B</u> Heater Current Heater-cathode Leakage Current Anode Current Screen Grid Current Mutual Conductance	Combined AQL Vhk = ± 90V Note 1	1.0 0.65 0.65 0.65 0.65 0.65	II II II II II	Ih Ihk Ihk Ia Ia Ig2 gn gn	0.41 - - 33 - 3.5 3.0 -	- - - 39 -	- - - 45 -	- - 5 51 -	0.49 - - - 7.5 5.2 -	13.3	A uA uA mA mA mA/V mA/V
	<u>GROUP C</u> g3 Continuity Power Output Reverse Grid Current Emission	Combined AQL Vg3 = 250V Note 2 RL = 5k Input signal = 8.8V r.m.s. Frequency = 1 kc/s Vh=6.3V; Va=350V; Vg2=305V; Ia=35mA; Rg1=500k; Note 3 Vg1 = Vg2 = Vg3 = Va = 30V	6.5 2.5 2.5 2.5 2.5	I I I I	 P out Ig1 Ia	 3.6 - 100	 - - -	 - - -	 - - -	 - - -		W uA mA
11.1	Vibration Noise Output	Va(b) = 250V Vg1 = -25V RL = 2k	2.5	I	Va AC	-	-	-	-	60		mV r.m.s.
	<u>GROUP D</u> Base Strain Capacitance	Measured on a 1 Mc/s bridge with the valve mounted in a fully screened socket. No shield.	6.5 6.5	II IC	 Cag1 C in C cut	 - 6.6 5.5	 - - -	 - - -	 - - -	 0.5 10.0 8.5		pF pF pF

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym- bol	Limits						Units
						Min	LAL	Dogey	UAL	MDX.	ALD	
	<u>GROUP E</u>											
11.2	Resonance Search	Va(b) = 250V Vg1 = -25V RL = 2k Frequency range = 25-500 c/s	2.5	IC								
	Vibration Noise Output Resonant Frequency				Va AC f	- 200	- -	- -	- -	Record -		mVrms c/s
11.3	Fatigue	Vh = 6.3V switched 1 min. on, 3 mins. off. Vh = Vg2 = 0 Min pk assal = 5g Frequency = 170 c/s Duration = 30,39,30 hrs.		IA								
	<u>Post Fatigue Tests</u>	Combined AQL	6.5									
	Vibration Noise	Note 4	2.5		Va AC	-	-	-	-	120		mVrms
	Heater-cathode Leakage Current	Vhk = + 90V	2.5		Ihk	-	-	-	-	40		uA
	Reverse Grid Current	Rg1 = 500k Max	2.5		Ig1	-	-	-	-	4.0		uA
	Power Output	Note 5	2.5		P out	2.3	-	-	-	-		W
11.4	Shock	Hammer angle = 30° No voltages		IA								
	<u>Post Shock Tests</u>	Combined AQL	6.5									
	Vibration Noise Output	Note 4	2.5		Va AC	-	-	-	-	120		mVrms
	Heater-cathode Leakage Current	Vhk = + 90V	2.5		Ihk	-	-	-	-	40		uA
	Reverse Grid Current	Rg1 = 500k Max	2.5		Ig1	-	-	-	-	4.0		uA
	Power Output	Note 5	2.5		P out	2.3	-	-	-	-		W
	<u>GROUP F</u>											
A VI/2	Life	Vg1=0 Rg1=100k - 500k Rk =270 ± 1%										
A VI/5.1	<u>Stability Life Test</u>											
	Change in Anode Current		1.0	I	Ia	-	-	-	-	7.5		%
	Change in Mutual Conductance		1.0	I	Δ gn	-	-	-	-	5		%
A VI/5.3.	Intermittent Life Test			IA								
	<u>Life Test End-point</u> (500 hours)		6.5									
A VI/5.6	Inoperatives Power Output	Note 5	2.5		P out	2.3	-	-	-	-		W
	Reverse Grid Current	Rg = 500k Max	2.5		Ig1	-	-	-	-	4.0		uA
	Heater-cathode Leakage Current	Vhk = ± 90V	2.5		Ihk	-	-	-	-	40		uA
	Mutual Conductance do Average change		2.5		Δ gn	2.55	-	-	-	5.2		uA/V

K1001	Test	Test Conditions	ACL %	Insp. Level	Sym- bol	Limits					Units
						Min.	LAL	Bogey	UAL	Max.	
A VI/ 5.6	Insulation	Vg1 - all = -100V	2.5		R	50	-	-	-	-	M
		Vg2 - all = -300V				50	-	-	-	-	M
		Va - all = -300V				50	-	-	-	-	M
	<u>Life Test End-point</u> (1000 hours)	10.0									
	Inoperatives Power Output	4.0 4.0		P out	2.0	-	-	-	-	W	
	Reverse Grid Current	Rg1 = 500k Max	4.0		Ig1	-	-	-	5.0	uA	
Heater-cathode Leakage Current Mutual Conductance	Vhk = ± 90V	4.0		Ihk	-	-	-	50	uA		
		4.0		gm	2.3	-	-	-	mA/V		
<u>GROUP C</u>											
A IX/ 2.5	Electrical re-test after 28-day holding period			1.00%							
A VI/ 5.6	Inoperatives		0.5								
	Reverse Grid Current	Rg1 = 500k Max	0.5		Ig1	-	-	-	2.0	uA	

NOTES

1. With Vg1 applied to Pins 1 and 2 in turn, Ia shall show no change.
2. During this test Ig2 shall rise when g3 is connected to g2.
3. Pre-heat for 5 minutes under the test conditions. During the test Ig1 shall not be rising or out of limit after 10 minutes.
4. The conditions for Vibration Noise specified in Group C shall apply.
5. The conditions for Power Output specified in Group C shall apply.