

Specification MOS/CV 4033 Issue 3 Dated 21.9.56 To be read in conjunction with K1001	<u>SECURITY</u>	
	<u>Specification</u> UNCLASSIFIED	<u>Valve</u> UNCLASSIFIED

TYPE OF VALVE - Reliable Double Triode with flexible leads CATHODE - Indirectly-heated ENVELOPE - Glass PROTOTYPE - CV455 - 12AT7 EQUIVALENT PINNED VALVE - CV4024	<u>MARKING</u>		
	K1001/4		
	<u>BASE</u>		
	B9A/F		
<u>RATING, CONNECTIONS, CAPACITANCES AND NOTES</u> See Specification MOS/CV4024 Issue 3 dated 21.9.56	<u>DIMENSIONS</u>		
	See K1001/A1/D11		
	Dimensions (mm)	Min	Max
	A. Seated height	-	49
B. Diameter	19	22.2	
D. Lead length	38	-	
	<u>MOUNTING POSITION</u>		
	Any		

TESTS

The tests required by specification MOS/CV4024 Issue 3 dated 21.9.56 shall be performed except as follows:-

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym-bol	Limits	Units
	<u>GROUP D</u>						
	DELETE -						
7.2	Base Strain	No voltages	6.5	IA			
	ADD -						
5.12	Lead Fragility	No voltages	6.5	IA			