

MINISTRY OF SUPPLY - DLRD/RREVALVE ELECTRONIC

CV4034

Specification MOS/CV4034 Issue 3 Dated 11.9.56 To be read in conjunction with K1001	<u>SECURITY</u>	
	<u>Specification</u> UNCLASSIFIED	<u>Valve</u> UNCLASSIFIED

TYPE OF VALVE - Reliable Double Triode with flexible leads CATHODE - Indirectly-heated ENVELOPE - Glass PROTOTYPE - CV491 - 12AU7 EQUIVALENT PINNED VALVE - CV4003	<u>MARKING</u> K1001/4	
	<u>BASE</u> B9A/F	
<u>RATING, CONNECTIONS, CAPACITANCES and NOTES</u> See Specification MOS/CV4003 Issue 4 Dated 11. 9. 56	<u>DIMENSIONS</u> See K1001/A1/D11	
	<u>Dimensions (mm)</u>	Min Max
	A. Seated height	- 49
B. Diameter	19 22.2	
D. Lead length	38 -	
<u>MOUNTING POSITION</u> Any		

TESTS

The tests required by Specification MOS/CV4003 Issue 4 Dated 11. 9. 56 shall be performed except as follows:-

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym- bol	Limits	Units
	<u>GROUP D</u> DELETE -						
7.2	Base Strain	No voltages	6.5	IA			
	<u>ADD -</u>						
5.12	Lead Fragility	No voltages	6.5	IA			