MINISTRY OF SUPPLY - DLRD/RRE VALVE ELECTRONIC V 4 0 9 0 Specification MOS/CV 4098 SECURITY Issue 1 Dated 14.7.59 Specification Valve Unclassified Unclassified To be read in conjunction with K1001, K1006, BS448 and BS1409 Indicates a change MARKING TYPE OF VALVE - Reliable RF Pentode, Flying Lead K1001/4 ENVELOPE - Glass CATHODE - Indirectly heated - CV4011, 5725/6AS6W BASE PROTOTYPE BS448: B7G/F/1.1 RATINGS AND CHARACTERISTICS DIMENSIONS BS.448: B7G/F/2.1/1 See Specification MOS/CV4011 Issue 2 dated 26.2.57 Dimensions (Ins) Min. Max. A. Seated height 0.666 0.733 C. Diameter E. Lead length 1.5 MOUNTING POSITION Any TESTS The tests required by specification MOS/CV4011, Issue 2, dated 26.2.57 shall be performed except as follows: -LIMITS TEST CONDITIONS AQLInsp. |Sym-K1001 TEST UNITS Level bol Min Bogey Max. DELETE. On page 2. under Degradation Rate Acceptance Tests. Clause 4.9.6.1 Base Strain ADD 6.5 IA No Voltages Lead Fragility 5.12 CV4098/1/1. Z.19678.