

Specification MOA/CV5333 Issue 1, dated 15.12.60 To be read in conjunction with K1001 B.S.448 and B.S.1409	<u>SECURITY</u>	
	<u>Specification</u> Unclassified	<u>Valve</u> Unclassified

TYPE OF VALVE - Pulse modulator tetrode. CATHODE - Indirectly heated. ENVELOPE - Glass. PROTOTYPE - CV4082.	<u>MARKING</u> See K1001/4
	<u>BASE</u> Phenolic B.S.448/B8-0/1.1

<u>RATINGS</u>	Note	<u>CONNECTIONS</u>		
Heater voltage. (V) 6.3 Heater current. (A) 1.32 Max. Anode voltage (DC). (KV) 1.5 Max. Anode voltage (Pulse). (KV) 1.5 Max. screen voltage (DC). (V) 800 Max. anode dissipation. (W) 15 Max. screen dissipation. (W) 3.5 Max. cathode current (Pulse). (A) 10.0 Max. cathode current (DC). (mA) 120 Max. anode current (Pulse). (A) 7.5 Max. peak heater cathode voltage (V) ± 150 Max. grid 1 cathode voltage. (V) ± 200 Max. grid 1 dissipation. (W) 0.5 Max. bulb temperature (C) 240 Inner amplification factor. $\mu(g1-g2)$ 7.5 Max. shock (short duration). (g) 500 Max. accn. (continuous). (g) 2.5	A	Pin		
		1	Int.Conn.	IC
		2	Heater	h
		3	Int.Conn.	IC
		4	Screen Grid	g2
		5	Control Grid	g1
		6	Int.Conn.	IC
		7	Heater	h
		8	Cathode	k
		T.C.	Anode	a
		<u>DIMENSIONS</u> See K1001/A1/D1		
		Dimension (mm)	Min.	Max.

<u>CAPACITANCES</u> (pF) (Note B)		B Diameter	-	34
Ca, g1 (nom) pF 1.0		A Overall Length	-	100
C in (nom) pF 18.5		L Seated Length	-	85
C out (nom) pF 12.5		<u>TOP CAP</u>		

<u>JOINT SERVICES CATALOGUE NO.</u> 5960-99-037-2304	B.S.448/CT1
<u>MOUNTING POSITION</u> Any	

<u>NOTES</u>
A. The temperature over the top of 15 mm of the bulb to be not greater than 150C.
B. Measured on 1 Mc/s bridge in fully screened holder. No shield. All IC connections left floating.

TESTS

- AA. To be performed in addition to those applicable in K1001 and in the specified order unless otherwise agreed with the Inspecting Authority.
- BB. This valve has a structure identical with that of the CV4082, but is fitted with a phenolic base.
- CC. K1001, section 17, shall apply to this valve. The sampling inspection tests which are performed on CV4082 valves may be used to qualify the CV5333 valves for acceptance, at the discretion of the manufacturer.

TEST CONDITIONS - unless otherwise stated :

Vh(V) Va(V) Vg2(V) Ia(mA)
 6.3 150 150 50

K1001	TEST	TEST CONDITIONS	AQL %	Insp Level	Sym-bol	LIMITS			Units
						Min.	Bogey	Max.	
5.2	<u>GROUP A</u>								
5.2	Insulation.	Vg1 - all = -100V		100%	R	100	-	-	M
		Vg2 - all = -300V		100%	R	100	-	-	M
		Va - all = -300V		100%	R	100	-	-	M
	Negative grid Current	Rg1 = 500k max.		100%	Ig1	-	-	2.5	µA
	<u>GROUP B</u>	Overall AQL	2.5						
	Heater current	Vhk = ± 100V	0.65	II	Ih	1.17	-	1.47	A
	Heater cathode Leakage current		0.65	II	Ihk	-	-	40	µA
	Negative grid Voltage		0.65	II	Vg1	10.5	-	16.5	V
	Screen current		0.65	II	Ig2	-	-	9.0	mA
	Mutual Conductance		0.65	II	gm	6.0	-	10.0	mA/V
	<u>GROUP C</u>	Overall AQL	6.5						
	Amplification Factor		2.5	I	µg1-g2	6.0	-	10.0	
	Anode current	Vg1 = -30V	2.5	I	Ia	-	-	600	µA
	Vibration noise Emission	Note 4	2.5	I	VaAC	-	-	75	mV
		A+g2+g1 strapped	2.5	I	IkpK	7.5	-	-	A
		Va pk = 250V							
		Note 2.							

K1001	TEST	TEST CONDITIONS	AQL %	Insp Level	Sym- bol	LIMITS			Units
						Min.	Bogey	Max.	
	<u>GROUP D</u> Capacitance	Measured on 1Mc/s bridge with valve in fully screened holder No shield Note 1	6.5	IC	Cag 1 C in C out	- - -	- - -	- - -	pF pF pF
11.3	<u>GROUP E</u> Fatigue	Vh = 6.9V Note 3		Ia					
11.4	Shock	No voltages Hammer angle = 30°		IA					
	<u>Post Fatigue and Shock Tests</u> Heater-cathode Leakage current	Vhk = ± 100V	2.5		Ihk	-	-	100	µA
	Negative grid Current	Rg1 = 500k max	2.5		Ig1	-	-	3	µA
	Mutual Conductance		2.5		gm	6.0	-	10	mA/V
	Vibration noise Current	Note 4.	2.5		Va AC	-	-	120	mVrms
<u>AVI/5</u>	<u>GROUP F</u> Life	Va = 500V Vg2 = 500V Ia = 30mA Vg1, adjust							
	<u>Life Test end point (500 hrs)</u>								
	Inoperatives Heater current		2.5		Ih	1.17	-	1.47	
	Heater-cathode Leakage Current	Vhk = ± 100V	6.5 6.5		Ihk	-	-	60	µA
	Reverse Grid Current	Rg1 = 500k max	6.5		Ig1	-	-	3	µA
	Mutual Conductance		6.5		gm	5.5	-	10	mA/V
	Emission Test	A+g2+g1 strapped Vapk = 250V Note 2	6.5		Ikp	6.0	-	-	A
	Electrode Insulation	See Group A	6.5		R	50	-	-	M

K1001	TEST	TEST CONDITIONS	AQL %	Insp Level	Sym-bol	LIMITS			Units
						Min.	Bogey	Max.	
	<u>GROUP G</u>								
A IX /2.5	Electrical retest after 28-day holding period.								
A VI /5.6	Inoperatives		0.5	100%					
	Reverse grid current	Rg1 = 500K max.	0.5	100%	Ig1	-	-	2.5	μ A

NOTES

- Capacity connections.

	HP	LP	E
C ag 1	TC	5	2. 4. 7. 8. C.
C in	5	2. 4. 7. 8.	TC. C.
C out	TC	2. 4. 6. 8.	5. C.

2. T_p 2 μ secs p.r.f. 50 c/s.
3. Valves to be vibrated in each of the three required planes for not less than 30 hrs. and not less than 100 hrs. total. Heater switched 1 min. on 3 mins. off. No other voltages applied. Min. peak acceleration = 5g. Frequency = 170 c/s.
4. Va (b) = 250V Rk = 270 ohms
 Vg2 (b) = 250V Ck = 1000 μ F
 RL = 2 Kohms Co = 0.1 μ F
 Rg2 = 15 Kohms g = 2.5