


TUNG-SOL

TRIODE PENTODE
MINIATURE TYPE



GLASS BULB

MINIATURE BUTTON

9 PIN BASE E9-1

OUTLINE DRAWING

JEDEC 6-3


COATED UNIPOTENTIAL CATHODE

HEATER

6.3 VOLTS 600 MA.

AC OR DC

ANY MOUNTING POSITION



BOTTOM VIEW
BASING DIAGRAM
JEDEC 9DX

THE 6AU8 IS A GENERAL-PURPOSE MINIATURE TUBE CONTAINING A SHARP CUT-OFF PENTODE AND A MEDIUM-MU TRIODE IN ONE ENVELOPE. EACH SECTION HAS ITS OWN CATHODE AND IS ELECTRICALLY INDEPENDENT. IT IS DESIGNED FOR USE IN 600 MA. SERIES HEATER OPERATED MONOCHROME AND COLOR TELEVISION RECEIVERS. THERMAL CHARACTERISTICS OF THE HEATER ARE CONTROLLED SUCH THAT HEATER VOLTAGE SURGES DURING THE WARM-UP CYCLE ARE MINIMIZED PROVIDED IT IS USED WITH OTHER TYPES THAT ARE SIMILARLY CONTROLLED. THE PENTODE SECTION IS PARTICULARLY SUITED FOR USE AS A VIDEO AMPLIFIER, VIDEO IF AMPLIFIER AND SOUND IF AMPLIFIER. THE TRIODE SECTION IS INTENDED FOR USE AS A SYNC AMPLIFIER, SEPARATOR OR CLIPPER OR AS A SWEEP OSCILLATOR.

DIRECT INTERELECTRODE CAPACITANCES
WITH NO EXTERNAL SHIELD

	PENTODE SECTION	TRIODE SECTION	
GRID TO PLATE	0.044	2.2	pf
INPUT	7.5	2.6	pf
OUTPUT	2.4	0.34	pf
PENTODE GRID #1 TO TRIODE PLATE	0.005		pf
TRIODE GRID TO PENTODE PLATE	0.002		pf
PENTODE PLATE TO TRIODE PLATE	0.12		pf

CONTINUED ON FOLLOWING PAGE

TUNG-SOL

CONTINUED FROM PRECEDING PAGE

RATINGS

INTERPRETED ACCORDING TO DESIGN CENTER SYSTEM



	PENTODE SECTION	TRIODE SECTION	
MAXIMUM HEATER-CATHODE VOLTAGE:			
HEATER NEGATIVE WITH RESPECT TO CATHODE TOTAL DC AND PEAK	200		VOLTS
HEATER POSITIVE WITH RESPECT TO CATHODE DC	100		VOLTS
TOTAL DC AND PEAK	200		VOLTS
MAXIMUM PLATE VOLTAGE	300	300	VOLTS
MAXIMUM GRID #2 SUPPLY VOLTAGE	300	---	VOLTS
MAXIMUM GRID #2 VOLTAGE	SEE RATING CHART		
MAXIMUM POSITIVE DC GRID #1 VOLTAGE	0	0	VOLTS
MAXIMUM PLATE DISSIPATION	3.0	2.5	WATTS
MAXIMUM GRID #2 DISSIPATION	1.0	---	WATTS
MAXIMUM GRID #1 CIRCUIT RESISTANCE:			
FIXED BIAS	0.25	0.5	MEGOHM
CATHODE BIAS	1.0	1.0	MEGOHM
HEATER WARM-UP TIME (APPROX.) ^A	11.0		SECONDS

^A HEATER WARM-UP TIME IS DEFINED AS THE TIME REQUIRED FOR THE VOLTAGE ACROSS THE HEATER TO REACH 80% OF ITS RATED VOLTAGE AFTER APPLYING 4 TIMES RATED HEATER VOLTAGE TO A CIRCUIT CONSISTING OF THE TUBE HEATER IN SERIES WITH A RESISTANCE OF VALUE 3 TIMES THE NOMINAL HEATER OPERATING RESISTANCE.

TYPICAL OPERATING CONDITIONS AND CHARACTERISTICS



CLASS A₁ AMPLIFIER



	PENTODE SECTION	TRIODE SECTION	
PLATE VOLTAGE	200	150	VOLTS
GRID #2 VOLTAGE	125	---	VOLTS
CATHODE BIAS RESISTOR	82	150	OHMS
AMPLIFICATION FACTOR	---	40	
PLATE RESISTANCE (APPROX.)	150 000	8 200	OHMS
TRANSCONDUCTANCE	7 000	4 900	μMHOS
PLATE CURRENT	15	9.0	MA.
GRID #2 CURRENT	3.4	---	MA.
GRID #1 VOLTAGE (APPROX.) FOR I _b = 100 μAMP.	-8	-6.5	VOLTS



PRINTED IN U. S. A.



6AU8







PRINTED IN U.S.A.

6AU8





PRINTED IN U. S. A.