

MINISTRY OF SUPPLY - DLRD/RRL

VALVE ELECTRONIC

CV4042

Specification MOS/CV4042 Issue 2 Dated 30th April, 1958 To be read in conjunction with K1001, BS448 & BS1409	<u>SECURITY</u>	
	<u>Specification</u> UNCLASSIFIED	<u>Valve</u> UNCLASSIFIED

Indicates a change ←

TYPE OF VALVE - Reliable High-vacuum, Half-wave Rectifier with flexible leads		<u>MARKING</u> See K1001/4	
CATHODE - Indirectly-heated		<u>BASE</u> E7G/F	
ENVELOPE - Glass		<u>CONNECTIONS</u>	
PROTOTYPE - CV 371		<u>CONNECTIONS</u>	
<u>RATING</u>		Lead	Electrode
All limiting values are absolute			
		Note	
Heater Voltage	(V)	4.0	
Heater Current	(A)	0.5	
→ Max. Anode Voltage (r.m.s.)	(kV)	2.0	
→ Max. Working Peak Inverse Voltage	(kV)	5.0	
→ Max. No-load Peak Inverse Voltage	(kV)	6.0	
Max. DC Output Current	(mA)	30	
Max. Heater-cathode Voltage	(V)	10	A
Max. Peak Cathode Current	(mA)	180	
Max. Reservoir Condenser (50 c/s)	(μF)	1.1	
→ Min. Limiting Impedance	(ohms)	4,500	
Min. H.T. Switching Delay for full rating	(secs)	20	
Max. Shock (short duration)	(g)	500	
Max. Acceleration (continuous operation)	(g)	2.5	
		<u>TOP C/P</u>	
See K1001/1/D5.2 and in addition a flexible lead 38 mm min. length			
<u>DIMENSIONS</u> See K1001/1/D11			
Dimension (mm)		Min.	Max.
A. Seated height		-	54
B. Diameter		.16	19
D. Lead length		38	-
<u>MOUNTING POSITION</u> Any			

NOTES

- A. The valve shall be operated with cathode connected to one side of the heater.
- B. Caution to Electronic Equipment Design Engineers: Special attention should be given to the temperature of valves to be operated in aircraft. Reliability will be seriously impaired if the maximum bulb temperature is exceeded. The life expectancy may be reduced if conditions other than those specified for life test are imposed on the valve and will be reduced appreciably if absolute maximum ratings are exceeded. Both reliability and performance will be jeopardised if heater voltage ratings are exceeded: life and reliability performance are directly related to the degree that regulation of the heater voltage is maintained at its centre-rated value.

TESTS

CV4042

To be performed in addition to those applicable in K1001

Test Conditions - unless otherwise specified									
		Vh (V)	Va (V)	C (uF)	Note 1				
		4.0	55	1.0					
K1001	Test	Test Conditions	AQL %	Insp. Level	Sym- bol	Limits			Units
						Min.	Bogey	Max.	
→ 7.1	Glass Strain	No voltages	6.5	I					
	<u>GROUP A</u> Voltage Break-down	Notes 2 and 3		100%					
	<u>GROUP B</u> Heater Current Anode Current Heater-cathode Leakage Current	Combined AQL Note 1 Vhk = 10V	1.0 0.65 0.65 0.65	II II II	Ih Ia Ihk	0.45 50 -	0.5 - -	0.55 - 10	A mA uA
	<u>GROUP C</u> 5.12 Lead Fragility	No voltages	6.5	IA					
→ 11.3	<u>GROUP D</u> Fatigue	Combined AQL Vh = 4.0V switched 1 min on, 3 mins off Va = 0 Min pk accel = 5g Frequency = 170 c/s Duration = 30, 39, 30 hrs.	6.5	IA					
	<u>Post Fatigue Tests</u> Voltage Break-down Heater Current Anode Current	Notes 2 and 3 Note 1	2.5 2.5 2.5		Ih Ia	0.45 48	- -	0.55 -	A mA
11.4	Shock	Hammer angle = 30° No voltages		IA					
	<u>Post Shock Tests</u> Voltage Break-down Heater Current Anode Current	Notes 2 and 3 Note 1	2.5 2.5 2.5		Ih Ia	0.45 48	- -	0.55 -	A mA

K1001	Test	Test Conditions	AQL %	Insp. Level	Sym- bol	Limits			Units
						Min.	Bogey	Max.	
	<u>GROUP E</u>								
A VI /5	Life	Note 2							
A VI /5.1	<u>Stability Life Test</u>			I					
	Change in Anode Current		1.0		Ia	-	-	10	%
A VI /5.3	Intermittent Life Test	Note 2			Ia				
	<u>Life Test End-point</u> (500 hrs)	Combined AQL	6.5						A
A VI /5.6	Inoperatives Heater Current		2.5						
	Anode Current	Note 1	2.5		Ih	0.45	-	0.55	A
			2.5		Ia	48	-	-	mA
	<u>GROUP F</u>								
A IX /2.5	Electrical retest after 28-day holding period			100%					
A VI /5.6	Inoperatives		0.5						

NOTES

- Alternatively, the valve may be tested at $I_a = 50\text{mA}$ when the following limits shall apply:
 - GROUP B: $V_a = 55\text{V max}$
 - GROUP D: Post Fatigue Tests: $V_a = 56.5\text{V max}$
Post Shock Tests : $V_a = 56.5\text{V max}$
 - GROUP E: Life Test: $V_a = 56.5\text{V}$
- The valve shall be tested in a half-wave rectifier circuit with 2.0 kV r.m.s. 50 c/s input applied through a total external impedance of 4,500 ohms including effective transformer impedance. The load resistance shall be adjusted to give 30 mA.
- The load conditions shall be maintained for 10 seconds, then the H.T. voltage shall be switched on and off 3 times at 5-second intervals. There shall be no persistent sparking, blue glow or distortion of the electrodes.