

Specification MOS/CV4045 Issue 2 Dated 6.11.56 To be read in conjunction with K1001, BS448 & BS1409	<u>SECURITY</u>	
	<u>Specification</u>	<u>Valve</u>
	UNCLASSIFIED	UNCLASSIFIED

→ Indicates a change

TYPE OF VALVE	- Reliable Beam Tetrode with flexible leads.	<u>MARKING</u>	
CATHODE	- Indirectly-heated	K1001/4	
ENVELOPE	- Glass	<u>BASE</u>	
PROTOTYPE	- CV2136	B9A/F	
EQUIVALENT PINNED VALVE	- CV4043 (VX7082)		
<u>RATING, CONNECTIONS, CAPACITANCES and NOTES</u>		<u>DIMENSIONS</u>	
See Specification MOS/4043, Issue 2, Dated 6.11.56		See K1001/AI/D11	
		Dimensions (mm)	Min    Max
		A. Seated height	-    60.5
B. Diameter	19    22.2		
D. Lead length	38    -		
		<u>MOUNTING POSITION</u>	
		Any	

TESTS

The tests required by Specification MOS/CV4043, Issue 2, Dated 6.11.56 shall be performed except as follows:-

K1001	Test	Test Conditions	ACL %	Insp. Level	Sym-bol	Limits	Units
7.2	<u>GROUP D</u> DELETE - Base Strain	No voltages	6.5	IA			
5.12	ADD - Lead Fragility	No voltages	6.5	IA			