

Issue 1 Dated 9.10.56

To be read in conjunction with Specification MOS(A)/ CV4068

Specification

Valve

UNCLASSIFIED

UNCLASSIFIED

<p>TYPE OF VALVE - Reliable Double Triode with flexible leads</p> <p>CATHODE - Indirectly Heated</p> <p>ENVELOPE - Glass</p> <p>PROTOTYPE - CV2212. <del>VX752C</del></p> <p>EQUIVALENT PINNED VALVE - CV4068</p>		<p><u>MARKING</u></p> <p>K1001/4</p>													
		<p><u>BASE</u></p> <p>B9A/F</p>													
<p><u>RATING, CONNECTIONS, CAPACITANCES and NOTES</u></p> <p>See Specification MOS(A)/ CV4068 Issue 1 Dated 8.10.56</p>		<p><u>DIMENSIONS</u></p> <p>See K1001/A1/D11</p> <table border="1"> <thead> <tr> <th>Dimensions (mm)</th> <th>Min.</th> <th>Max.</th> </tr> </thead> <tbody> <tr> <td>A seated height</td> <td>-</td> <td>49.0</td> </tr> <tr> <td>B diameter</td> <td>19.0</td> <td>22.2</td> </tr> <tr> <td>D lead length</td> <td>38.0</td> <td>-</td> </tr> </tbody> </table>		Dimensions (mm)	Min.	Max.	A seated height	-	49.0	B diameter	19.0	22.2	D lead length	38.0	-
Dimensions (mm)	Min.	Max.													
A seated height	-	49.0													
B diameter	19.0	22.2													
D lead length	38.0	-													
		<p><u>MOUNTING POSITION</u></p> <p>Any</p>													
<p><u>TESTS</u></p> <p>The tests required by Specification MOS(A)/CV4068 Issue 1 Dated 8.10.56 shall be performed except as follows</p>															
K1001	Test	Test Conditions	AQL %	Insp. Level	Symbol	Limits	Units								
	<u>GROUP D</u>														
	<del>DELETE:-</del>														
7.2	Base Strain	No voltages	6.5	IA											
	<del>ADD:-</del>														
5.12	Lead Fragility	No voltages	6.5	IA											