

Specification MOS(A)/CV 4079 Issue 1. Dated 1st May, 1958 To be read in conjunction with K.1001 and BS 448	<u>SECURITY</u>	
	<u>Specification</u> UNCLASSIFIED	<u>Valve</u> UNCLASSIFIED

TYPE OF VALVE - Reliable Low Impedance Triode CATHODE - Indirectly-heated ENVELOPE - Glass PROTOTYPE - VX 3208 EQUIVALENT FLEXIBLE LEAD VALVE - CV 4038 <u>RATING, CONNECTIONS, CAPACITANCES and NOTES</u> See Specification MOS(A)/CV 4038, Issue 3, dated 6.11.56.	<u>MARKING</u> K.1001/4		
	<u>BASE</u> B9A		
	<u>DIMENSIONS</u> See K1001 A1/D4		
	Dimension (mm)	Min.	Max.
	L. Seated height	-	66
B. Diameter	19	22.2	
A. Overall length	-	73	
<u>MOUNTING POSITION</u> Any			

TESTS

The tests required by Specification MOS(A)/CV 4038, Issue 3, dated 6.11.56. shall be performed except as follows:-

K1001	Test	Test Conditions	AQL %	Insp. Level	Symbol	Limits	Units
	<u>GROUP D</u>						
	DELETE -						
5.12	Lead Fragility	No voltages	6.5	IA			
	ADD -						
7.2	Base Strain	No voltages	6.5	IA			